




Complete Downstream Equipment for Extrusion Lines

NPS-HD *Dual Servo Pullers*

- Precision, dual servo drive belt traction assemblies
- Compression force setting with digital force display
- Multi-V drive pulleys



NPS-STD *Servo Pullers*

- Precision servo connected to a right-angle gearbox that drives a dual-serpentine belt.
- Poly-V drive and driven pulleys ensure consistent pulling traction.



NC-5-HD-HS *High Speed Servo Rotary Knife Cutter*

- 5" Dia./ 4.5" x 7.5" cut capacity
- Maximum continuous cuts (2 blades) of 2300 CPM
- Maximum peak torque (in/lb) of 4550



NC-5-HD *Servo Rotary Knife Cutter*

- 5" Dia./ 4.5" x 7.5" cut capacity
- Maximum continuous cuts (1 blade) of 700 CPM
- Maximum on-demand cuts (1 blade) of 150 CPM @ 400 RPM



C-SERIES *Servo Rotary Knife Cutter*

- 2" - 4" cut capacity
- Maximum continuous cuts (1 blade) of 750 - 800 CPM
- Maximum on-demand cuts (1 blade) of 200 - 300 CPM @ 600 RPM




NPC-STD *Puller/ Cutters*

- Precision, servo drive belt traction assemblies
- Manually adjustable compression force setting
- Multi-V drive pulleys
- 2", 3" or 4" rotary knife cutter



NS-6 *Up-Cut Servo Traveling Extrusion Saw*

- 6" cut capacity
- Provides optimum cutting of a wide range of extrudate
- 7" color touch PLC ensures easy set-up and recipe management



NVT *Vacuum* & **NCT** *Cooling Tanks for pipe & profile*

- Equipped for ease of operation and high performance with complete filtration system
- Vacuum tanks have modulating stepper valve and VFD closed loop vacuum control with blower style pumps
- Integral sump tray

