

UNIVERSAL 1023 PIGMENTS

UNIVERSAL 1023 PIGMENTS

may be used to integrally color Umaco Universal 1023. Each pigment pack is pre-measured so all you need to do is simply blend one pigment pack with a 50# bag of Universal 1023 Gray in order to achieve the desired color.

DOSAGE

One 1# Universal 1023 Pigment Pack per each 50# bag of Universal 1023

MIXING

For best results, dry-blend one 1# Universal 1023 Pigment Pack with a 50# bag of Universal 1023 in a 5G pail until the batch is of uniform color and free of streaks. Gradually add 4-1/2 to 5 quarts of clean potable water. Mixing completely for 1-2 minutes to form a creamy, lump free consistency that is of uniform color and free of streaks. Let rest for 2 minutes then remix. For best results, mechanical mixing is

preferred using a 1/2" drill (500-650 rpm) with a jiffy mixer. Only mix enough material that can be placed within 15-20 minutes.

Universal 1023 Retarder

For a slower set time, add (1) packet to each 50# bag while mixing.

APPLICATION

Apply as indicated on the Universal 1023 data sheet. Follow instructions as listed per the specific application.

PRECAUTIONS

- Apply only when the ambient and surface temperatures are between 45° F - 85°F and will remain so for at least 24 hours after application
- Do not apply if rain, snow or any other precipitation is expected within 24 hours
- Concrete surfaces subject to high levels of moisture vapor transmission should be treated with Umaco Hydro-

Stop 25 prior to application to prevent discoloration, delamination or a complete loss of bond

- All control and expansion joints must be carried through
- Always adhere to local building codes and regulations when using this product

CAUTION

All colors are non-toxic. Avoid breathing dust and wash hands and skin thoroughly after handling. For specific handling precautions and first aid procedures refer to the Safety Data Sheet.


24 Hour Emergency Medical/Spill Information (Chemtrec): 800-424-9300

KEEP OUT OF THE REACH OF CHILDREN.


For technical assistance call
978-453-8881

www.umaco.com

Colors presented on the color chart below are just a representation of the actual color. For an exact color, request to see color swatch.



Gray (out of bag)



White (out of bag)



Yello Ochre



Limeproof Brown



Deep Cement Buff



Raw Umber



Van Dyke Brown



Terra Cotta



Brownstone



Limeproof Black



Phone: 978-453-8881
Toll Free: 800-442-5535
Fax: 978-453-2416
www.umaco.com