

WFG60P

6,000 Lb.

LPG Pneumatic Tire

*Specifications &
Features*



3.0 Ton IC Forklift



WFG60P



Authorized Distributor

General	1	Model			WFG60 EPA		
	2	Power Type			LPG		
	3	Rated Capacity		Lbs	6000		
	4	Load Centre		Inch	24		
Characteristic&Dimension	5	* Lift Height		Inch	118		
	6	* Fork Size	L×W×T	Inch	42×5×1.8		
	7	Mast Tilt Angle	F/R	Deg	6°/12°		
	8	Front Overhang (Wheel center to fork face)		Inch	18.7		
	9	Ground Clearance (Bottom of mast)		Inch	5.3		
	10	Overall Dimension	Length to face of fork(Without fork)		Inch	107	
	11		Overall Width		Inch	48	
	12		Mast Lowered Height		Inch	83	
	13		Mast Extended Height (with backrest)		Inch	164	
	14		Overhead Guard Height		Inch	82	
	15	Turning Radius (outside)		Inch	96		
	16	Min. intersecting aisle		Inch	98		
Performanc	17	Speed	Travel (Empty load)		Mp/h	12	
	18		Lifting(Full load)		In/s	17	
	19	Max.Gradeability		%	20		
Chassis	20	* Tire	Front			28×9-15-12 PR	
	21		Rear			6.50-10-10 PR	
	22	Wheelbase		In	67		
	23	Service weight		Lbs	9480		
Power&Transmission	24	Battery	Voltage/Capacity		V/A h	12/80	
	25	* Engine	Model			K25	
	26		Manufacture			NISSAN	
	27		Rated output/r.p.m.		kw	42 / 2700	
	28		Rated torque/r.p.m.		N·m	185 / 1350	
	29		No.of Cylinder			4	
	30		Bore×Stroke		mm	89 x 100	
	31		Displacement		cc	2488	
	32		Fuel Tank Capacity		G	16	
	33	*	Type			Hydraulic	
	34	Transmission	Stage	FWD/RVS			1/1
	35	Operating Pressure for attachment		PSI		2538	

Features & Benefits

- Nissan K25 Tier IV approved,, Nodular iron crankshaft for increase strength, world-class engine sealing system for superior leak protection. Sintered powdered-metal exhaust valve seats for enhanced durability and noise reduction. Cast Iron block, cast iron head and cast iron manifold. •

- Power shift (Automatic) transmission with separate inching and brake pedals, offers positive operation in tight working areas, especially beneficial working on ramps and inclines.

- High visibility design mast with side thrust rollers in the carriage for smoother operation and longer life of the mast components.

- Fully Hydrostatic Power Steering for smoother operation and many fewer parts for lower maintenance costs. This utilizes the largest cylinder and thickest steel for protection of any forklift in its class!

- Large hydraulically actuated Drum & Shoe type brakes for positive braking performance and ease of maintenance. Mechanical lever type parking brake for reliability.

- Control Handles are mounted on the dash for operator convenience and also allows the operator to enter/exit the operator compartment from either side of the machine comfortably.

- Tilt Steering Wheel
- Adjustable Seat
- Seat Belt
- Dual Head Lights
- Front Turn Signals
- Rear Turn Signals
- Brake Lights
- Back-up Lights
- Back-up Alarm
- Neutral Safety Switch
- Welded Overhead Guard
- Integral Gas Tank
- Integral Hydraulic Tank
- High air intake
- Cyclone air cleaner
- Insulated engine cover
- Hand hold for entry
- Radiator overflow bottle
- Third valve & lever
- Horn
- Hour Meter
- Charge warning light
- Temperature warning light
- Oil pressure gauge
- Key switch
- Safety load backrest
- ITA Class III forks and carriage
- Easy access floor boards
- Rubber safety mat
- Meet or exceed all ANSI B56.1 safety standards for powered industrial trucks and Underwriters Laboratories requirements as to fire hazard.
- EPA Compliant



WFG60P



Standard Equipment

- Two Stage Mast
- Cushion Tires
- Nissan K25
- Cummins Diesel
- Tier IV Interim
- AutoTransmission
- Headlights
- Back Up Lights
- Turn Signals Hydro
- Steer Axle Mirrors
- Load Backrest
- Seat Belt
- Tilt Steer Wheel
- 3rd Valve
- Operator Manual
- Standard Forks



Optional Equipment

- Various Masts
- Standard
- Full Free Lift
- Triplex
- Tires
- Solid Pneumatic
- Foam Filled
- Side Shifter**
- 4 way hydraulics**



WFG60P