

Sample	Location	Copper (Cu)	Zinc (Zn)	Tin (Sn)	Lead (Pb)	Iron (Fe)	Silicon (Si)
1M							
	1 Top dial cover	80.776	16.463				
	2 Underside dial	81.086	16.467				
	3 Left bolt	91		6.458			
	4 Body (Front)	89.059	2.556	5.675	1.44		
	5 Body (Back)	87.599	2.975	5.908	2.186		
2M							
	1 Top dial cover	64.68	25.07				3.92
	2 Underside dial	66.6	25.717				3.397
	3 Left bolt	84.961	2.672	7.217	3.338		
	4 Body (Front)	84.153	1.116	10.925	2.471		
	5 Body (Back)	86.557	1.593	8.944	1.675		
	6 Top bolt (grey)			1.264	57.76	1.242	3.984
	7 Top bolt (brown)	2.25				63.02	2.143
3M							
	1 Top dial cover	88.434	1.515	7.098	2.328		
	2 Underside dial	88.04		7.32	2.67		
	3 Dial housing	87.907	1.488	7.336	2.648		
	4 Top pin	72.1	17.24		1.583		1.931
	5 Body (Front)	86.414	1.58	7.712	3.18		
	6 Body (Back)	88.893	1.247	7.22	2.01		
	7 Top bolt	70.763	26.058		1.567		
4M							
	1 Side housing	84.997	2.81	6.703	2.1		
	2 Body (Front)	77.563	1.337	9.361	7.801	1.223	
	3 Body (Back)	77.728	2.216	8.916	7.376	1.467	
	4 Bolt (Corroded)	85.584	2.047	8.011	2.22		
	5 Bolt (Clean)	85.723	2.481	8.107	1.817		
	6 Side housing	83.735	3.667	7.878	2.77		
	7 Glass dial						30.18

Aluminium (Al) Magnesium (Mg) Sulphur (S) Arsnic (As) Cadmium (Cd) Nickel (Ni) Calcium (Ca)

2.31
2.04

1.4

1.24
1.26

1.19

27.812

3.507

1.36

1.5

2.624

1.322

1.316

9.845

Light Elements Misc.

	~3
	~3
	~2.5
	~1.3
	~1.3
	~2.5
	~2.5
	~1.8
	~0.5
	~1.3
	~1.9
28.27	~1.8
	~0.7
	~2
	~0.6
	~3
	~1
	~0.7
	~1.6
	~3
	~1.393
	~2.297
	~2.138
	~1.872
	~1.95
59.1	~0.875