

PAVER-SAVER

PROTECTS & ADDS YEARS OF LIFE TO YOUR INVESTMENT

REPELS WATER, OIL & STAINS

- Advanced nano technology
- Repels water, oil & stains
- Excellent beading properties
- Penetrating & breathable
- Clear, minimal change in substrate appearance
- Low VOC
- UV Stable
- Mitigates moisture & efflorescence transfer
- Improves freeze-thaw stability
- Resists biological growth & chemical degradation
- Horizontal & vertical surfaces
- Cost effective & easy to apply
- May be applied to a wide variety of mineral substrates such as concrete, pavers, stucco, natural stone, clay tile & brick.



Toll Free: 800-442-5535
Phone: 978-453-8881
www.umaco.com

Natural Looking, Easy to Apply & Safe to Use

Paver-Saver, which is formulated using nano-technology, is a premium, deep-penetrating, water-based aliphatic polyurethane designed to repel water, oil and stains.

Paver-Saver Plus mechanically & chemically bonds to a wide variety of mineral substrates including, but not limited to, concrete pavers, concrete slabs, stucco, natural stone, clay tile & brick.

Paver-Saver adds life to your investment by protecting the surface from the damaging effects of water, oils, staining, ice-melting products & freeze-thaw cycles.



Paver-Saver Application

Concrete surfaces must be cured (28 days), sound, clean, dry and untreated with previous coatings. Remove all dirt, dust, spalling or loose concrete, oil, grease, wax, mildew, efflorescence, laitance, curing compounds, form release agents, rust, paint or any other foreign material which might effect the bond. **SEE WARNING REGARDING PAINT REMOVAL.** Umaco Ultra-Clean may be used to remove oil or grease stains from concrete surfaces and may also be used as an all purpose cleaner for surface preparation. Using a scrub brush, work Ultra-Clean into the concrete and let stand for 5 minutes. Then rinse completely with water and allow to dry. Repeat if necessary. Neutralizing not required.

Etching

A rough profile is recommended for proper adhesion which may be obtained by lightly etching the concrete using Umaco Ultra-Etch. Apply generously at full strength then let it work into the concrete for 10 minutes. Rinse thoroughly with water and allow to dry. Neutralizing not required. Ultimately, a porous surface is required for the material to bond properly. Test by sprinkling some water on the surface. If the water is quickly absorbed, the surface is ready. If the water beads up, further preparation is required. Contact a Umaco representative for more information regarding proper surface preparation.

APPLICATION

Paver-Saver can be applied using a brush, roller, pump-up, HVLP or airless spray. This product is best suited for application in temperatures between 50°F to 95°F.

Spray

Spray on in a fine, fog pattern to form a thin continuous film. Avoid puddling in low areas. If puddles occur, brush or roll them out. Additional application may be required to ensure substrate has achieved full saturation.

Roller

Roll onto substrate using a 3/8 inch non-shed roller cover via a dip and roll method. Material can also be poured onto the substrate

and distributed. Do not allow excess puddles. If puddles occur, brush or roll them out. Additional applications may be required to ensure substrate has achieved full saturation.

Brush

Utilize traditional bristle brush application for more controlled application to corners, control joints and grout lines.

RECOAT

Paver-Saver has indefinite inter-coat adhesion to itself. Older slabs or very porous substrates may require additional applications to ensure substrate has achieved full saturation. Allow initial coat to dry before applying additional coat.

CURING

Optimal curing condition is 73°F, Relative Humidity 50% and air-flow. Repellency begins to develop within 24 hours, completed in one week. Beading generally improves with time.

COVERAGE

Approximate coverage is 200 ft² per gallon. Coverages will vary depending on surface porosity, profile and application method.

CLEANUP

While still wet, clean up equipment with soap and water.

DISPOSAL

Dispose of empty packaging and other waste in accordance with federal, state, provinces and local regulations

STORAGE

Paver-Saver has a shelf life of one (1) year from date of manufacture in original, factory-sealed containers when stored indoors at a temperature between 60-90°F (15-32°C).

LIMITATIONS

- Do not apply on wet or damp substrate
- Do not apply when substrate has direct sun (high noon)
- Apply when ambient and surface temperatures are between 50°F-95°F
- Substrate temperature must be 5° F above dew point

- New concrete must cure 28 days
- Do not apply over non-porous, smooth troweled or previously coated substrates

TECHNICAL DATA

Solids by Volume: 9.7%

VOC's: 23.5 g/l

Color: Milky white, dries clear

Coverage per Gallon: 200 ft²/gal

Flash Point: > 200°F

WARNING

Harmful if inhaled. Harmful if swallowed. May cause eye irritation. May cause allergic skin reaction. Before using, read the Safety Data Sheet and follow all precautions to prevent bodily harm.

WARNING! If you scrape, sand or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead. Wear a properly fitted respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

For technical assistance call 978-453-8881.

www.umaco.com



Surface Preparation Products




UMACO ULTRA-CLEAN

An environmentally safe, 100% biodegradable solution used to clean concrete, concrete pavers & retaining wall block. Ultra-Clean safely & effectively removes dirt, oil, grease & grime. Helps clean & prepare concrete surfaces prior to the application of Paver-Saver. Neutralizing not required



UMACO ULTRA-ETCH

An environmentally safe, 100% biodegradable, non-fuming solution used to lightly etch non-porous concrete. Ultra-Etch takes the place of harmful & hazardous acids yet provides excellent results. Helps prepare concrete surfaces prior to the application of Paver-Saver. Neutralizing not required.



UMACO UNIVERSAL 1023

A cementitious, high-density, patching, resurfacing and underlayment material for applications from a feather-edge up to 6". Helps repair & prepare concrete surfaces (if needed) prior to the application of Paver-Saver. Available in gray and white.



60 Rear Newhall Street
Lowell, MA 01852
Toll Free: 800-442-5535
Phone: 978-453-8881
www.umaco.com